

# EV2041-SD

## Broadcast 4 x 1 SD SDI Switcher



Features:

Compact design

Glitch free switching

Optional re-clocked  
inputs

Mains powered

# EV2041-SD 4 x 1 Switcher

## BROADCAST 4 x 1 SDI Matrix

The EV2041-SD is a four input stand alone SDI routing matrix housed in a self contained small 180 x 190 x 40mm box. The standard unit comes with four single inputs, one output and a local control panel. The options available are re-clocked looping inputs and a dual output, also available as an option is external GPI or RS232 control. The EV2041-SD has been designed to full EBU 3267-E & SMPTE 259M specifications and switches on line 6, but will switch immediately if required.

## Specification

<b>VIDEO</b>	<ul style="list-style-type: none"><li>• Input impedance 75 Ohm</li><li>• Nominal Input Level 800mv</li></ul>
<b>INPUTS</b>	<ul style="list-style-type: none"><li>• BNC</li></ul>
<b>OUTPUTS</b>	<ul style="list-style-type: none"><li>• BNC</li></ul>
<b>POWER</b>	<ul style="list-style-type: none"><li>• Mains Input IEC</li><li>• Power supply 90 to 250V Integral</li><li>• Power consumption 15 Watts</li><li>• Operating temperature 0 to +40 degrees Celsius</li></ul>
<b>CASE</b>	<ul style="list-style-type: none"><li>• Package Height Width Depth Weight</li><li>• SW271 40mm 180mm 190mm 1Kg</li></ul>
<b>CONNECTOR TYPES</b>	<ul style="list-style-type: none"><li>• Video BNC</li><li>• Remote controls D9 female</li><li>• Power (mating supplied) IEC</li></ul>



**Electronic Visuals Limited**  
20 Ferry Lane, Wraysbury,  
Staines, Middlesex,  
England TW19 6HG

Tel: +44 (0)1784 483311  
Fax: +44 (0)1784 483918  
Email: [info@electronic-visuals.com](mailto:info@electronic-visuals.com)  
Web site: [www.electronic-visuals.com](http://www.electronic-visuals.com)